



Features

- SLC-NAND flash technology
- Support True IDE mode
- Master/Slave selectable
- Support S.M.A.R.T. command set
- Support C.H.S. / LBA customization
- Support Power Loss Protection
- Capacities from 8GB up to 128GB

Specification

- **Compatibility** ATA/ATAPI-8 and True IDE mode
- **Declarations** RoHS & REACH compliant
- **Flash technology** SLC-NAND flash technology
- **Form-factor** Rugged Metal 2.5" PATA (IDE) SSD
- **Host Interface** Standard 44-pin PATA (IDE) male connector
- **Master/Slave** By jumper
- **Performance**
 - **Data transfer rate** PIO 0~4, MWDMA 0~2, UDMA 0~6
 - **Sequential read** 106.1 MB/sec (Max.)
 - **Sequential write** 98.3 MB/sec (Max.)
- **Environmental**
 - **Operating temp.** STD. 0°C~+70°C/IND. -40°C~+85°C
 - **Non-operating temp.** STD. -20°C~+80°C/IND. -50°C~+95°C
 - **Humidity** 10% ~ 95% non-condensing
 - **Vibration** 70 Hz to 2K Hz, 15G, 3 axes
 - **Shock** 0.5ms, 1500 G, 3 axes
 - **Altitude** 70,000 feet
- **Power consumption**

- **Power requirement** +5V ± 5%
- **Reading mode** 190 mA (Max.)
- **Writing mode** 230 mA (Max.)
- **Idle mode** 5.7 mA (Max.)
- **Reliability**
 - **Wear-leveling** Global wear-leveling algorithms
 - **TBW** Up to 628 TBW at 128GB Capacity (Client workload by JESD-219A)
- **MTBF** > 3,000,000 hours
- **Erase counts** Up to 60,000 times
- **ECC** 72 bits per 1024 bytes block
- **Physical specification**
 - **Weight (Max.)** 75g
 - **Dimension (WxLxH)** 70.10 x 100.00 x 8.80 (mm)
- **Conformal coating** Optional
- **Warranty**
 - **SLC STD. grade** 3 years or within 60,000 erasing counts
 - **SLC IND. grade** 5 years or within 60,000 erasing counts

Part Number List

Capacity	0°C~+70°C	Capacity	-40°C~+85°C
8GB	SR2IF008G-MQCTC-U	8GB	WR2IF008G-MQITI-U
16GB	SR2IF016G-MQCTC-U	16GB	WR2IF016G-MQITI-U
32GB	SR2IF032G-MQCTC-U	32GB	WR2IF032G-MQITI-U
64GB	SR2IF064G-MQCTC-U	64GB	WR2IF064G-MQITI-U
128GB	SR2IF128G-MQCTC-U	128GB	WR2IF128G-MQITI-U

Part Number Decoder

X1	X2	X3	X4	X5	X6	X7	X8	X9	X10	X11	X12	X13	X14	X15	X16	X17	X18	X19	X20
----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Example

W	R	2	I	F	1	2	8	G	-	M	Q	I	T	I	-	U	C		
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	--

X1 Grade

S : Standard grade operating temp. 0°C~+70°C
 W: Industrial grade operating temp. -40°C~+85°C

X2 The material of casing

R : Rugged metal casing

X3 X4 X5 Product category

2IF : 2.5" 9.0 mm height PATA (IDE) SSD

X6 X7 X8 X9 Capacity

- 008G : 8GB
- 016G : 16GB
- 032G : 32GB
- 064G : 64GB
- 128G : 128GB

X11 Controller

M : HERCULES Series

X12 Controller version

A, B, C, D.....

X13 Controller grade

C : Commercial grade
 I : Industrial grade

X14 Flash IC brand

T : Toshiba SLC-NAND flash IC

X15 Flash IC grade

C : Commercial grade
 I : Industrial grade

X17 Data transfer rate / Disk type

U : Defaulted as UDMA-6 mode / Fixed disk type
 P : Optional as PIO-4 mode / Fixed disk type
 A : Optional as Autosense UDMA or PIO mode /Fixed disk type

X18 X19 X20 Reserved for specific requirements

C : Conformal coating (optional)

SLC

aSLC

MLC

3D-NAND

DRAM Module

Adapter

Card-drive